Technical Data Sheet



2/13/2015

Model: VSA9510ZXG

Version: N/A

Product Description

Type: Scroll

Application: CBP - Commercial Back

Pressure

Refrigerant: R-404A

Voltage/Frequency: 460V 3~ 60Hz 380-420V 3~

50Hz



Product Specifications

General

Evaporating Temp. Range:-17.8°C to 10°C (0°F to 50°F) **Motor Torque:**High Start Torque (HST)

Compressor Cooling: Fan

Mechanical

Weight: 71
Weight Unit of Measure: LB
Displacement (cc): 26.55
Oil Type: Polyolester
Viscosity (cSt): 24

Viscosity (cSt): 24
Oil Charge (cc): 710

Electrical

Voltage Range (50 Hz): 342-462 Voltage Range (60 Hz): 414-506 Locked Rotor Amps (LRA): 21 Rated Load Amps (RLA 50 Hz): 2.79 Rated Load Amps (RLA 60 Hz): 2.79 Max. Continuous Current (MCC in Amps): 4.6 Motor Resistance (Ohm) - Main: 8.83 Motor Resistance (Ohm) - Start: N/A **Motor Type:** 3PH Overload Type: N/A N/A **Relay Type:**

Agency Approval

cURus Recognized